

ICC
MATERIAL SAFETY DATA SHEET

DATE OF PREP
11/30/04

MANUFACTURER

NAME: ICC
ADDRESS: 32400 AURORA ROAD
CITY-STATE: SOLON OHIO
ZIPCODE: 44139

EMERGENCY TELEPHONE NO.
DAY: 440-248-8288
NIGHT: 800-424-9300
INFO: 440-248-8288

SECTION 1 --- PRODUCT

NUMBER: TH0426 – E-Z Clean Graffiti Remover
NAME : * **E-Z CLEAN GRAFFITI REMOVER**
CLASS : SOLVENT BASED
UN NUMBER - 1263

H M I S HAZARD CODES
HEALTH: 2 - MODERATE
FLAMMABILITY: 3 - SERIOUS
REACTIVITY: 0 - MINIMAL
PROTECTIVE EQUIPMENT:

SECTION II ---- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	-- C.A.S. --
MATERIAL DESCRIPTION	BY WGT.	Registry No.
TOLUENE	43.67	108883
METHYL ETHYL KETONE	40.46	78933
ISOPROPYL ALCOHOL	15.84	67630

SECTION III ---PHYSICAL DATA

BOILING RANGE : 175.°F – 230.°F (79.44°C – 110.°C)
VAP. PRESSURE : 21. @ 68.°F (20.°C)
78. @ 68.°F (20.°C)
EVAPORATION RATE : Faster than N-Butyl Acetate
VAPOR DENSITY : HEAVIER THAN AIR
% Volatile by Weight : 100. %
% Volatile by Volume : 100. %
SPECIFIC GRAVITY : 0.83013
VOC MAX LBS/GAL & GRMS/LTR: 6.9/830.0

SECTION IV --- FIRE AND EXPLOSION HAZARD DATA

OSHA Flammability Class: IB
FLASHPOINT : 31.°F (-0.56°C)
SETA FLASH
EXPLOSIVE RANGE: 1.1%
12.7%

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, WATER FOG, AND CARBON DIOXIDE
UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep this product away from heat, sparks, flame, and other sources of ignition. Keep containers closed when not in use. Closed containers may burst when exposed to extreme heat or fire. Toxic gases may form when product is exposed to extreme heat. Product may decompose under fire.
SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool and protect exposed containers. Use self-contained breathing apparatus. Water may be ineffective in extinguishing a paint fire. Stream of water may spread the flame. If water is used, fog nozzles are preferable.
HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS: Carbon Monoxide, carbon dioxide, oxides of nitrogen, acrid fumes, phosphorous, oxygen, toxic gases

SECTION V ---- HEALTH HAZARD DATA

INHALATION: If affected, remove to fresh air. If breathing stops, give artificial respiration. Administer oxygen if available. Get immediate medical assistance.
SKIN CONTACT: Flush immediately with plenty of water followed by washing with soap and water. Remove contaminated clothing. Wash contaminated clothing before reuse. If irritation occurs, consult a physician.
EYE CONTACT: Flush immediately with large amounts of water, especially under the lids for at least 15 minutes. If irritation or other effects persist, obtain medical assistance.
INGESTION: If swallowed, do not induce vomiting. Drink two glasses of water to dilute. Obtain medical assistance immediately.
PRIMARY ROUTE(S) OF EXPOSURE: Inhalation, skin contact, eye contact, and ingestion. Depending on conditions of use. To minimize exposure, follow recommendations for proper use, Handling, ventilation, and personal protective equipment.
EFFECTS OF OVEREXPOSURE
INHALATION: Irritation of respiratory tract. Prolonged inhalation may lead to loss of appetite, mucous membrane irritation, fatigue, drowsiness, dizziness, and/or lightheadedness, Headache, loss of coordination, nausea, vomiting, chest pain, coughing, nervous system depression, intoxication, confusion, anesthetic effect or narcosis, difficulty of Breathing, allergic response, asthmatic reaction, tremors, severe lung irritation or damage, liver damage, pulmonary edema, convulsions, pneumoconiosis, loss of Consciousness, asphyxiation, death. Possible sensitization to respiratory tract. Sanding dust inhalation may cause lung damage.
CHRONIC INHALATION: CONTAINS ISOCYANATES: To avoid breathing vapor spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Do not breathe vapor or mist. Wear eye protection, gloves, and protective clothing while mixing activator with enamel, during application, and until all vapors and spray mist are exhausted. Individuals with chronic respiratory or prior respiratory reactions to isocyanates must not be exposed to mists or vapors containing isocyanates.
SKIN CONTACT: Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting, blistering and severe skin irritation. Skin contact may result in dermal adsorption of component(s) of this product, which May cause drowsiness, dizziness, and/or lightheadedness.
EYE CONTACT: Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis, blurred vision, tearing of eyes, and redness of eyes, severe eye irritation, and corneal injury.
INGESTION: Ingestion may cause lung inflammation and damage due to aspiration of material into lungs, mouth and throat irritation, drowsiness, dizziness and/or lightheadedness, headache, nausea, vomiting, diarrhea, gastro-intestinal disturbances, abdominal pain, central nervous system depression, intoxication, anesthetic effect or narcosis, liver damage, kidney damage, pulmonary edema, loss of consciousness.
MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: None generally expected when recommendations for proper use, handling, ventilation, and personal protective equipment are followed.

SECTION VI --- STABILITY & REACTIVITY DATA

STABILITY: THIS PRODUCT IS STABLE
HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur
MATERIALS TO AVOID: Oxidizers, acids, hypochlorites, mineral acids, nitrates, hydrazine per formic acid, bromine pentafluoride, bases.
CONDITIONS TO AVOID: Elevated Temperatures, contact with oxidizing agent, sparks, open flame, ignition sources.

SECTION VII – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Eliminate all sources of ignition. Ventilate area. Avoid breathing vapors. Use appropriate personal protective equipment. Use self-contained breathing apparatus if Necessary. Contain spill and remove with inert absorbent. Use non-sparking tools. Use proper containers. Prevent material from entering sewers, natural ways, or soil.
WASTE DISPOSAL
Dispose in accordance with all applicable local, county, state, and federal regulations. Do not incinerate closed containers. If necessary, use only a licensed facility/firm.

SECTION VIII ---- EXPOSURE CONTROLS/PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

Table with 6 columns: Substance, ACGIH TLV, ACGIH TLV-C, ACGIH STEL, OSHA STEL, OSHA PEL. Rows include Toluene, Methyl Ethyl Ketone, and Isopropyl Alcohol.

GENERAL PRECAUTIONS TO BE TAKEN IN USE: Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

RESPIRATORY PROTECTION: If personal exposure cannot be controlled below applicable limits by ventilation, wear an appropriate properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA (Canadian z94.4).

VENTILATION: Provide dilution, ventilation, or local exhaust to maintain the level of vapors and dust below the applicable limits. Use only non-sparking explosion proof equipment.

PERSONAL PROTECTIVE EQUIPMENT: Splash goggles or safety glasses with side shields, impervious gloves, impervious clothing, and chemical resistant boots for spill clean up.

HYGIENIC PRACTICES: Wash clothing before reuse. Wash hands before eating, smoking, or using washroom.

HMS RATINGS: Ratings are only suggested. The contractor/employer has the ultimate responsibility to evaluate the hazard that this product represents in the environment in which it is used.

RATING SYSTEM: 0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe *=Chronic Effects

PERSONAL PROTECTIVE EQUIPMENT: this code is left blank. It should be entered by the contractor/employer who is familiar with the actual conditions under which this product is ultimately used.

SECTION IX ----HANDLING & STORAGE/ SPECIAL PRECAUTIONS

HANDLING & STORAGE: Store in cool, dry, and well-ventilated area. Keep away from heat, sparks, and open flame. Keep from freezing. Keep containers tightly closed and upright when not in use.

OTHER PRECAUTIONS: Use only with adequate ventilation. Use appropriate respiratory protection. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes. Avoid breathing vapors, spray mist, or sanding dust.

SECTION X - ADDITIONAL INFORMATION

SARA TITLE III SECTION 313 (40CFR372)

This product contains a substance (s) that may be subject to the reporting requirements.

Table with 3 columns: Ingredient Name, Weight %, CAS Number. Rows include Toluene, Methyl Ethyl Ketone, and Isopropyl Alcohol.

CALIFORNIA PROPOSITION 65:

This product contains a substance (s) known to the state of California to cause cancer and adverse reproductive toxicity.

Table with 3 columns: Ingredient Name, Weight %, CAS Number. Row includes Toluene.

As of the date of this MSDS, all of the components in this product are listed (or otherwise exempt from listing) on the TSCA inventory. This MSDS complies with OSHA hazard communication standard 29 CFR 1910.1200.

The above information pertains to the products as currently formulated and is based on the information received from raw material suppliers and other sources. We believe, to the best of our knowledge, information, and belief, the information contained herein to be accurate and reliable as of the date of the Material Safety Data Sheet.

CEPA: All substances in this product are on the Canadian Domestic Substance List.

SARA Title III - Section 304 CERCLA (40CFR302.4) :

This product contains a substance (s) subject to release notification.