

K. Coatings, LLC  
MATERIAL SAFETY DATA SHEET

DATE OF PREP  
07/07/07

MANUFACTURER

NAME: K. Coatings, LLC  
ADDRESS: 32400 AURORA ROAD  
CITY-STATE: SOLON OHIO  
ZIPCODE: 44139

EMERGENCY TELEPHONE NO.  
DAY: 440-248-8288  
NIGHT: 800-424-9300  
INFO: 440-248-8288

SECTION 1 --- PRODUCT

NUMBER: TH0003 - E-Z Clean Reducer  
NAME : \* **E-Z CLEAN Reducer**  
CLASS : SOLVENT BASED  
UN NUMBER - 1263

**H M I S HAZARD CODES**  
HEALTH: 2 - MODERATE  
FLAMMABILITY: 3 - SERIOUS  
REACTIVITY: 0 - MINIMAL  
PROTECTIVE EQUIPMENT:

SECTION II ---- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	C.A.S.
MATERIAL DESCRIPTION	BY WGT.	Registry No.
ACETIC ACID 2METHOXY 1METHYLET	53.79	108656
METHYL ETHYL KETONE	26.85	78933
TOLUENE	11.31	108883
XYLENE	6.47	1330207
ETHYLBENZENE	1.54	100414

SECTION III ---PHYSICAL DATA

BOILING RANGE : 175.°F - 293.°F (79.44°C - 145.°C)  
VAP. PRESSURE : 6.7 @ 70.°F (21.11°C)  
78. @ 68.°F (20.°C)  
EVAPORATION RATE : Faster than N-Butyl Acetate  
VAPOR DENSITY : HEAVIER THAN AIR  
% Volatile by Weight : 100. %  
% Volatile by Volume : 100. %  
SPECIFIC GRAVITY : 0.90062  
VOC MAX LBS/GAL & GRMS/LTR: 7.48/898.3

SECTION IV --- FIRE AND EXPLOSION HAZARD DATA

OSHA Flammability Class: IB  
FLASHPOINT : 45.°F (7.22°C)  
SETA FLASH  
EXPLOSIVE RANGE: 0.8%  
11.4%

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, WATER FOG, AND CARBON DIOXIDE

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep this product away from heat, sparks, flame, and other sources of ignition. Keep containers closed when not in use. Closed containers may burst when exposed to extreme heat or fire. Toxic gases may form when product is exposed to extreme heat. Product may decompose under fire.

SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool and protect exposed containers. Use self-contained breathing apparatus. Water may be ineffective in extinguishing a paint fire. Stream of water may spread the flame. If water is used, fog nozzles are preferable.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS: Carbon Monoxide, carbon dioxide, oxides of nitrogen, acrid fumes, phosphorous, oxygen, toxic gases

SECTION V ---- HEALTH HAZARD DATA

INHALATION: If affected, remove to fresh air. If breathing stops, give artificial respiration. Administer oxygen if available. Get immediate medical assistance.

SKIN CONTACT: Flush immediately with plenty of water followed by washing with soap and water. Remove contaminated clothing. Wash contaminated clothing before reuse. If irritation occurs, consult a physician.

EYE CONTACT: Flush immediately with large amounts of water, especially under the lids for at least 15 minutes. If irritation or other effects persist, obtain medical assistance.

INGESTION: If swallowed, do not induce vomiting. Drink two glasses of water to dilute. Obtain medical assistance immediately.

PRIMARY ROUTE(S) OF EXPOSURE: Inhalation, skin contact, eye contact, and ingestion. Depending on conditions of use. To minimize exposure, follow recommendations for proper use, Handling, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE

INHALATION: Irritation of respiratory tract. Prolonged inhalation may lead to loss of appetite, mucous membrane irritation, fatigue, drowsiness, dizziness, and/or lightheadedness, Headache, loss of coordination, nausea, vomiting, chest pain, coughing, nervous system depression, intoxication, confusion, anesthetic effect or narcosis, difficulty of Breathing, allergic response, asthmatic reaction, tremors, severe lung irritation or damage, liver damage, pulmonary edema, convulsions, pneumoconiosis, loss of Consciousness, asphyxiation, death. Possible sensitization to respiratory tract. Sanding dust inhalation may cause lung damage.

CHRONIC INHALATION: CONTAINS ISOCYANATES: To avoid breathing vapor spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Do not breathe vapor or mist. Wear eye protection, gloves, and protective clothing while mixing activator with enamel, during application, and until all vapors and spray mist are exhausted. Individuals with chronic respiratory or prior respiratory reactions to isocyanates must not be exposed to mists or vapors containing isocyanates.

SKIN CONTACT: Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting, blistering and severe skin irritation. Skin contact may result in dermal adsorption of component(s) of this product, which May cause drowsiness, dizziness, and/or lightheadedness, headache, loss of coordination, blurred vision, central nervous system depression, confusion.

EYE CONTACT: Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis, blurred vision, tearing of eyes, and redness of eyes, severe eye irritation, and corneal injury.

INGESTION: Ingestion may cause lung inflammation and damage due to aspiration of material into lungs, mouth and throat irritation, drowsiness, dizziness and/or lightheadedness, headache, nausea, vomiting, diarrhea, gastro-intestinal disturbances, abdominal pain, central nervous system depression, intoxication, anesthetic effect or narcosis, liver damage, kidney damage, pulmonary edema, loss of consciousness.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: None generally expected when recommendations for proper use, handling, ventilation, and personal protective equipment are followed.

Contains Ethyl Benzene a substance which has been classified as possibly carcinogenic to Humans by IARC.

SECTION VI --- STABILITY & REACTIVITY DATA

STABILITY: THIS PRODUCT IS STABLE

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur

MATERIALS TO AVOID: Oxidizers, acids, hypochlorites, mineral acids, nitrates, hydrazine per formic acid, bromine pentafluoride, bases.

CONDITIONS TO AVOID: Elevated Temperatures, contact with oxidizing agent, sparks, open flame, ignition sources.

**SECTION VII – ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Eliminate all sources of ignition. Ventilate area. Avoid breathing vapors. Use appropriate personal protective equipment. Use self-contained breathing apparatus if necessary. Contain spill and remove with inert absorbent. Use non-sparking tools. Use proper containers. Prevent material from entering sewers, natural ways, or soil.

**WASTE DISPOSAL**

Dispose in accordance with all applicable local, county, state, and federal regulations. Do not incinerate closed containers. If necessary, use only a licensed facility/firm.

**SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION**

**OCCUPATIONAL EXPOSURE LIMITS**

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
ACETIC ACID 2METHOXY 1METHYLET	N/EST	N/EST	N/EST	N/EST	N/EST
METHYL ETHYL KETONE	200.00 PPM	N/EST	300.00 PPM	300.00 PPM	200.00 PPM
TOLUENE	50.00 PPM	N/EST	N/EST	150.00 PPM	100.00 PPM
XYLENE	100.00 PPM	N/EST	150.00 PPM	150.00 PPM	100.00 PPM
ETHYLBENZENE	100.00 PPM	N/EST	125.00 PPM	125.00 PPM	100.00 PPM

**GENERAL PRECAUTIONS TO BE TAKEN IN USE:** Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using. Product may contain substances classified as nuisance particulates that may be hazardous levels only during sanding or abrading of the dried film.

**RESPIRATORY PROTECTION:** If personal exposure cannot be controlled below applicable limits by ventilation, wear an appropriate properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA (Canadian z94.4). When sanding or abrading a dried film, wear a dust/mist respirator approved by NIOSH/MSHA (Canadian z94.4) for dust, which may be generated from this product, the underlying product, or the abrasive.

**VENTILATION:** Provide dilution, ventilation, or local exhaust to maintain the level of vapors and dust below the applicable limits. Use only non-sparking explosion proof equipment. Discharge exhaust only in an area away from ignition sources.

**PERSONAL PROTECTIVE EQUIPMENT:** Splash goggles or safety glasses with side shields, impervious gloves, impervious clothing, and chemical resistant boots for spill clean up.

**HYGIENIC PRACTICES:** Wash clothing before reuse. Wash hands before eating, smoking, or using washroom.

**HMIS RATINGS:** Ratings are only suggested. The contractor/employer has the ultimate responsibility to evaluate the hazard that this product represents in the environment in which it is used.

**RATING SYSTEM:** 0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe \* =Chronic Effects

**PERSONAL PROTECTIVE EQUIPMENT:** this code is left blank. It should be entered by the contractor/employer who is familiar with the actual conditions under which this product is ultimately used.

**SECTION IX – HANDLING & STORAGE/ SPECIAL PRECAUTIONS**

**HANDLING & STORAGE:** Store in cool, dry, and well-ventilated area. Keep away from heat, sparks, and open flame. Keep from freezing. Keep containers tightly closed and upright when not in use. Do not puncture or re-use containers. Transfer only to approved containers with complete and appropriate labeling. Containers should be grounded when pouring.

**OTHER PRECAUTIONS:** Use only with adequate ventilation. Use appropriate respiratory protection. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes. Avoid breathing vapors, spray mist, or sanding dust. Empty containers may contain hazardous residues. Wash hands thoroughly after handling, especially before eating or smoking.

**SECTION X - ADDITIONAL INFORMATION**

**SARA TITLE III SECTION 313 (40CFR372)**

This product contains a substance (s) that may be subject to the reporting requirements.

Ingredient Name:	Weight %	CAS Number
METHYL ETHYL KETONE	26.85	78933
TOLUENE	11.31	108883
XYLENE	6.47	1330207
ETHYLBENZENE	1.54	100414

**CALIFORNIA PROPOSITION 65:**

This product contains a substance (s) known to the state of California to cause cancer and adverse reproductive toxicity.

Ingredient Name:	Weight %	CAS Number
TOLUENE	11.31	108883

**CEPA:** All substances in this product are on the Canadian Domestic Substance List.

As of the date of this MSDS, all of the components in this product are listed (or otherwise exempt from listing) on the TSCA inventory. This MSDS complies with OSHA hazard communication standard 29 CFR 1910.1200.

The above information pertains to the products as currently formulated and is based on the information received from raw material suppliers and other sources. We believe, to the best of our knowledge, information, and belief, the information contained herein to be accurate and reliable as of the date of the Material Safety Data Sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the user's consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data and to comply with all applicable international, federal, state, and local laws and regulations.

As of the date of this MSDS, all of the components in this product are listed (or otherwise exempt from listing) on the TSCA inventory. This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulation) and the MSDS contains all the information required by the CPR.

**SARA Title III – Section 304 CERCLA (40CFR302.4) :**

This product contains a substance (s) subject to release notification.