



Technical Data
EZ - Clean®
Graffiti Remover
TH-0426

DESCRIPTION: A mixture of solvents designed to remove most graffiti from surfaces painted with EZ - Clean® Anti-Graffiti Coating.

SOLVENT TYPE: Aromatic Hydrocarbons

FLASH POINT: 45°F Seta Flash

WEIGHT PER GALLON: 7.25 lbs.

SHELF LIFE: Minimum 12 months

MIXING: No mixing necessary

PACKAGE: 1 Gallon "F" Styles Cans – 6 per case

SAFETY INFORMATION: ***FLAMMABLE! HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. SKIN AND EYE IRRITANT. CONTAINS AROMATIC HYDROCARBONS.*** Keep away from heat, sparks, and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin or eyes. ***FIRST AID:*** If swallowed, do not induce vomiting. Call physician immediately. In case of eye contact, immediately flush thoroughly with water and call a physician. For skin contact, wash thoroughly. ***USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. NOTICE:*** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

HMIS VALUE: H = 2 F = 2 R = 0 PP = F

All technical data, recommendations and services are accurate at the date of issuance but are subject to change without prior notice. Seller assumes no responsibility for the results obtained or damages incurred from their use by the Buyer in whole or in part. No warranty, including those of merchantability or fitness for a particular purpose, is expressed or implied since the method of application and its use is beyond our control. There are no warranties that extend beyond the description or the face hereof.

K. Coatings, LLC
32400 Aurora Road * P.O. Box 391699
Solon, Ohio 44139
Ph: (440) 248-8288 * Fax: (440) 349-2267